



- Replacement kit includes new style recessed masthead.
 - Mast is 2-1/2" longer to accommodate the new mast head.
 - Holes for masthead / upper shroud tang bolt are pre-drilled.
- Note: Do not drill additional holes through the mast for the upper shroud tangs at their original locations. They need the additional support of the masthead assembly.
- Masthead will need to be drilled for the compression sleeve.
 - Upper shroud tangs will be 1-3/8" higher than those on the original mast. If there is not enough adjustment in the turnbuckles, use the included rigging toggles that provide an additional 1-1/4" in length.
 - Upper shroud tangs, bolt, compression sleeve, and nylock nut are included.
 - Holes for mast step bolt must be drilled during assembly.
 - New, mast step, mast step fasteners, mast step bolt, and nut to match the new mast section are included in the kit.
 - Machined for sail entrance slot, no hardware is installed. Internal halyards will require modification to install exit blocks at base of the mast.
 - New spreaders, brackets, compression sleeve, tangs, bolt, pop rivets, and nylock nut for lower shroud attachment are included.

- a) Bottom of mast to top of sail track gate, in inches
b) Bottom of mast to bottom of sail track gate, in inches

This is a special order item; your order cannot be cancelled or returned once your order is accepted, so please choose and measure carefully. Complete your order by agreeing to these terms and signing below.

I, _____,
printed name

understand and agree that some modification by myself or my representative may be required to achieve a proper fit of this kit and certify that the dimensions for the sail track gate are correct.

X _____ Date _____
signature