

# Keel Bolt Torque Schedule

**Check with boat on the hard and about 70% of the boat's total weight on the keel**

Boat	K-Bolt Diameter	Torque ft-lb	Socket Size
CP-16	1/2" - 13	39	3/4"
CP-18	1/2" - 13	39	3/4"
CP-22	1/2" - 13	39	3/4"
CP-25	1/2" - 13	39	3/4"
C-22	1/2" - 13	39	3/4"
CP-26	5/8" - 11	83	15/16"
C-25	5/8" - 11	83	15/16"
C-250	5/8" - 11	83	15/16"
C-27	5/8" - 11	83	15/16"
C-270	5/8" - 11	83	15/16"
CP-30	3/4" - 10	105	1 1/8"
C-28	3/4" - 10	105	1 1/8"
C-30	3/4" - 10	105	1 1/8"
C-34	3/4" - 10	105	1 1/8"
C-36	3/4" - 10	105	1 1/8"
C-38	3/4" - 10	105	1 1/8"
C-400 (aft only, 1 bolt)	3/4" - 10	105	1 1/8"
CP-37	1" - 8	235	1 1/2"
C-320	1" - 8	235	1 1/2"
C-375	1" - 8	235	1 1/2"
C-400 (remaining 10 bolts)	1" - 8	235	1 1/2"
C-42	1" - 8	235	1 1/2"